







# Three Phase String Inverter

SUN-30/33/35/36K-G04



-  2 MPP trackers, Max. efficiency up to 98.6%
-  Zero export application, VSG application
-  String intelligent monitoring (optional)
-  Wide output voltage range
-  Anti-PID function (Optional)

## Technical Data

Model	SUN-30K-G04	SUN-33K-G04	SUN-35K-G04	SUN-36K-G04
<b>Input Side</b>				
Max. DC Input Power (kW)	39	42.9	45.5	46.8
Max. DC Input Voltage (V)	1000			
Start-up DC Input Voltage (V)	250			
MPPT Operating Range (V)	200-850			
Max. DC Input Current (A)	40+40			
Max. Short Circuit Current (A)	60+60			
No. of MPP Trackers	2			
No. of Strings per MPP Tracker	3+3			
<b>Output Side</b>				
Rated Output Power (kW)	30	33	35	36
Max. Active Power (kW)	33	36.3	38.5	39.6
Rated Output Voltage/Range (V)	3L/N/PE 220/380V, 230/400V 0.85Un-1.1Un (this may vary with grid standards)			
Rated Grid Frequency (Hz)	50 / 60 (Optional)			
Operating Phase	Three Phase			
Rated AC Grid Output Current (A)	45.5/43.5	50/47.8	53/50.7	54.5/52.2
Max. AC Output Current (A)	50/47.9	55/52.6	58.3/55.8	60/57.4
Power Factor Adjustment Range	0.8 leading to 0.8 lagging			
Total Harmonics Current Distortion (THDi)	<3%			
DC Injection Current (mA)	<0.5%			
Grid Frequency Range	45-55 or 55-65 (Optional)			
<b>Efficiency</b>				
Max. Efficiency	98.6%			
Euro Efficiency	97.8%			
MPPT Efficiency	>99%			
<b>Protection</b>				
DC Reverse-Polarity Protection	Yes			
AC Short Circuit Protection	Yes			
AC Output Overcurrent Protection	Yes			
Output Overvoltage Protection	Yes			
Insulation Resistance Protection	Yes			
Ground Fault Monitoring	Yes			
Anti-islanding Protection	Yes			
Temperature Protection	Yes			
Integrated DC Switch	Yes			
Remote Software Upload	Yes			
Remote Change of Operating Parameters	Yes			
Surge Protection	DC Type II / AC Type II			
<b>General Data</b>				
Cabinet Size (WxHxD mm)	362x577x215 (Excluding Connectors and Brackets)			
Weight (kg)	23			
Topology	Transformerless			
Internal Consumption	<1W (Night)			
Running Temperature	-25 to +65°C, >45°C Derating			
Ingress Protection	IP65			
Noise Emission (Typical)	≤50 dB			
Cooling Concept	Smart Cooling			
Permissible Altitude (m)	2000			
Warranty	5 Years			
Grid Connection Standard	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105			
Operating Surroundings Humidity	0-100%			
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			
<b>Features</b>				
Display	LCD1602			
Interface	RS485/RS232/Wifi/LAN			