

MOD 3000~9000TL3-X

- Max. efficiency 98.6%
- OLED and Touch button
- Type II SPD on DC and AC side
- String Monitoring
- AFCI optional



GROWATT

P O W E R
- I N G O
T O M O -
R R O W O

Datasheet	MOD 3000TL3-X	MOD 4000TL3-X	MOD 5000TL3-X	MOD 6000TL3-X	MOD 7000TL3-X	MOD 8000TL3-X	MOD 9000TL3-X
Input data (DC)							
Max. recommended PV power (for module STC)	4500W	6000W	7500W	9000W	10500W	12000W	13500W
Max. DC voltage	1100V						
Start voltage	160V						
Nominal voltage	580V						
MPPT voltage range	140V-1000V						
No. of MPP trackers	2						
No. of PV strings per MPP tracker	1						
Max. input current per MPP tracker	13A						
Max. short-circuit current per MPP tracker	16A						
Output data (AC)							
AC nominal power	3000W	4000W	5000W	6000W	7000W	8000W	9000W
Max. AC apparent power	3300VA	4400VA	5500VA	6600VA	7700VA	8800VA	9900VA
Nominal AC voltage (range*)	220V/380V, 230V/400V (340-440V)						
AC grid frequency (range*)	50/60 Hz (45-55Hz/55-65 Hz)						
Max. output current	5.0A	6.7A	8.3A	10.0A	11.7A	13.3A	15.0A
Adjustable power factor	0.8leading...0.8lagging						
THDi	<3%						
AC grid connection type	3W+N+PE						
Efficiency							
MAX. efficiency	98.3%	98.3%	98.3%	98.3%	98.6%	98.6%	98.6%
European efficiency	97.5%	97.5%	97.5%	97.5%	98.1%	98.1%	98.1%
MPPT efficiency	99.9%						
Protection devices							
DC reverse polarity protection	Yes						
DC Switch	Yes						
AC/DC surge protection	Type II / Type II						
Insulation resistance monitoring	Yes						
AC short-circuit protection	Yes						
Ground fault monitoring	Yes						
Grid monitoring	Yes						
Anti-islanding protection	Yes						
Residual-current monitoring unit	Yes						
String fault monitoring	Yes						
AFCI protection	Optional						
General data							
Dimensions (W / H / D)	425/387/147mm	425/387/147mm	425/387/147mm	425/387/147mm	425/387/178mm	425/387/178mm	425/387/178mm
Weight	12.5kg	12.5kg	12.5kg	12.5kg	14kg	14kg	14kg
Operating temperature range	- 25°C ... +60°C						
Nighttime power consumption	< 1W						
Topology	Transformerless						
Cooling	Natural convection						
Protection degree	IP66						
Relative humidity	0–100%						
Altitude	4000m						
DC connection	H4/MC4(Optional)						
AC connection	Connector						
Display	OLED+LED/WIFI+APP						
Interfaces: USB/RS485/WIFI/GPRS/LAN/RF	yes/yes/Optional/Optional/Optional/Optional						
Warranty: 5 / 10 years	Yes/Optional						
CE, VDE0126, Greece, EN50549, C10/C11, UTE C 15-712, IEC62116, IEC61727, IEC 60068, IEC 61683, CEI0-21, N4105, TOR Erzeuger G98/G99, G100, AS4777, UNE21 7001, UNE206007, PO12.2							

* The AC voltage range and frequency range may vary depending on specific country grid standard.
All specifications are subject to change without notice.

MOD 10~15KTL3-X

- Max. efficiency 98.6%
- OLED and Touch button
- Type II SPD on DC and AC side
- String Monitoring
- AFCI optional



P O W E R
- I N G O
T O M O -
R R O W O

GROWATT

www.ginverter.com

Datasheet	MOD 10KTL3-X	MOD 11KTL3-X	MOD 12KTL3-X	MOD 13KTL3-X	MOD 15KTL3-X
Input data (DC)					
Max. recommended PV power (for module STC)	15000W	16500W	18000W	19500W	22500W
Max. DC voltage	1100V				
Start voltage	160V				
Nominal voltage	580V				
MPPT voltage range	140V-1000V				
No. of MPP trackers	2				
No. of PV strings per MPP tracker	1	1	1/2	1/2	1/2
Max. input current per MPP tracker	13A	13A	13/26A	13/26A	13/26A
Max. short-circuit current per MPP tracker	16A	16A	16/32A	16/32A	16/32A
Output data (AC)					
AC nominal power	10000W	11000W	12000W	13000W	15000W
Max. AC apparent power	11000VA*	12100VA	13200VA	14300VA	16500VA
Nominal AC voltage (range*)	220V/380V, 230V/400V (340-440V)				
AC grid frequency (range*)	50/60 Hz (45-55Hz/55-65 Hz)				
Max. output current	16.7A	18.3A	20A	21.7A	25A
Adjustable power factor	0.8leading...0.8lagging				
THDI	<3%				
AC grid connection type	3W+N+PE				
Efficiency					
MAX. efficiency	98.6%				
European efficiency	98.1%	98.1%	98.2%	98.2%	98.2%
MPPT efficiency	99.9%				
Protection devices					
DC reverse polarity protection	Yes				
DC Switch	Yes				
AC/DC surge protection	Type II / Type II				
Insulation resistance monitoring	Yes				
AC short-circuit protection	Yes				
Ground fault monitoring	Yes				
Grid monitoring	Yes				
Anti-islanding protection	Yes				
Residual-current monitoring unit	Yes				
String fault monitoring	Yes				
AFCI protection	Optional				
General data					
Dimensions (W / H / D)	425/387/178mm				
Weight	14kg	14kg	16kg	16kg	16kg
Operating temperature range	- 25°C ... +60°C				
Nighttime power consumption	< 1W				
Topology	Transformerless				
Cooling	Natural convection				
Protection degree	IP66				
Relative humidity	0~100%				
Altitude	4000m				
DC connection	H4/MC4(Optional)				
AC connection	Connector				
Display	OLED+LED/WIFI+APP				
Interfaces: USB/RS485/WIFI /GPRS/LAN/RF	yes/yes/Optional/Optional/Optional/Optional				
Warranty: 5 / 10 years	Yes/Optional				
CE, VDE0126, Greece, EN50549, C10/C11, UTE C 15-712, IEC62116, IEC61727, IEC 60068, IEC 61683, CEI0-21, N4105, TOR Erzeuger G98/G99, G100, AS4777, UNE217001, UNE206007, PO12.2					

* For Belgium C10/C11, MOD 10KTL3-X max. output power is limit to 10000VA.

* The AC voltage range and frequency range may vary depending on specific country grid standard. All specifications are subject to change without notice.